


P-Channel Enhancement MOSFET

Features

- $V_{DS} (V) = -20V$
- $I_D = -3.5 A$
- $R_{DS(ON)} < 75m\Omega (V_{GS} = -10V)$
- $R_{DS(ON)} < 95m\Omega (V_{GS} = -4.5V)$
- $R_{DS(ON)} < 145m\Omega (V_{GS} = -2.5V)$



Marking Code

YFW3419

A19T

Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	-20	V
Gate-Source Voltage	V_{GS}	± 12	V
Continuous Drain Current *1 TA=25°C	I_D	-3.5	A
Current *1 TA=70°C		-2.8	
Pulsed Drain Current *2	I_{DM}	-15	
Power Dissipation *1 TA=25°C	P_D	1.4	W
TA=70°C		0.9	
Thermal Resistance.Junction-to-Ambient	$R_{\theta JA}$	125	°C/W
Thermal Resistance.Junction-to-Case	$R_{\theta JC}$	60	°C/W
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	°C

*1The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz.

Copper, in a still air environment with $T_A = 25^\circ C$

*2 Repetitive rating, pulse width limited by junction temperature.

Electrical Characteristics (Ta=25°C unless otherwise specified.)

Parameter	Symbol	Testconditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	V _{DSS}	I _D =250 μ A, V _{GS} =0V	-20			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-16V, V _{GS} =0V			-0.5	μ A
		V _{DS} =-16V, V _{GS} =0V, T _J =55°C			-2.5	
Gate-Body leakage current	I _{GSS}	V _{DS} =0V, V _{GS} =± 10V			± 1	μ A
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} I _D =-250 μ A	-0.7	-0.9	-1.4	V
Static Drain-Source On-Resistance	R _{DS(ON)}	V _{GS} =-10V, I _D =-3.5A		59	75	m Ω
		V _{GS} =-10V, I _D =-3.5A T _J =125°C		83	105	
		V _{GS} =-4.5V, I _D =-3A		76	95	
		V _{GS} =-2.5V, I _D =-1A		111	145	
On state drain current	I _{D(ON)}	V _{GS} =-4.5V, V _{DS} =-5V	-15			A
Forward Transconductance	g _{FS}	V _{DS} =-5V, I _D =-3.5A		6.8		S
Input Capacitance	C _{iss}	V _{GS} =0V, V _{DS} =-10V, f=1MHz		512	620	pF
Output Capacitance	C _{oss}			77		pF
Reverse Transfer Capacitance	C _{rss}			62		pF
Gate resistance	R _g	V _{GS} =0V, V _{DS} =0V, f=1MHz		9.2	13	Ω
Total Gate Charge	Q _g	V _{GS} =-4.5V, V _{DS} =-10V, I _D =-3.5A		5.5	6.6	nC
Gate Source Charge	Q _{gs}			0.8		nC
Gate Drain Charge	Q _{gd}			1.9		nC
Turn-On DelayTime	t _{D(on)}	V _{GS} =-10V, V _{DS} =-10V, R _L =2.8 Ω, R _{GEN} =3 Ω		5		ns
Turn-On Rise Time	t _r			6.7		ns
Turn-Off DelayTime	t _{D(off)}			28		ns
Turn-Off Fall Time	t _f			13.5		ns
Body Diode Reverse Recovery Time	t _{rr}	I _F =-3.5A, di/dt=100A/μs		9.8	12	ns
Body Diode Reverse Recovery Charge	Q _{rr}	I _F =-3.5A, di/dt=100A/μs		2.7		nC
Maximum Body-Diode Continuous Current	I _S				-2	A
Diode Forward Voltage	V _{SD}	I _S =-1A, V _{GS} =0V	-0.65	-0.81	-0.95	V

Typical Characteristics




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

Typical Characteristics




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note F)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note F)




Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)

Ordering information


Package	Packing Description	Base Quantity	Packing Quantity
SOT23-3L	Tape/Reel, 7" reel	3000pcs/Reel	24000PCS/Box 120000PCS/Carton

Package Dimensions

SOT23-3L

Dim.	Millimeter (mm)		mil	
	Min.	Max.	Min.	Max.
A	1.05	1.25	41	49.2
A1	0.10		3.93	
A2	1.05	1.15	41	45
b	0.30	0.50	12	20
c	0.10	0.20	3.93	7.9
D	2.82	3.02	111	119
E	1.50	1.70	59	67
E1	2.65	2.95	104	116
e	0.95		37.4	
e1	1.80	2.00	71	78
L	0.30	0.066	12	26
Θ	8°			

The recommended mounting pad size



Disclaimer

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.