

**SiC Schottky Barrier Rectifier**

**Reverse Voltage - 1200V**

**Forward Current - 10 A**

**Features**


- ◆ Reverse withstand voltage 1200V
- ◆ Zero reverse recovery current
- ◆ High working frequency
- ◆ Switch characteristics are not affected by temperature
- ◆ Fast switching speed
- ◆ Positive temperature coefficient of positive pressure drop

**Advantages**

- ◆ Very low switching loss
- ◆ Higher efficiency
- ◆ Low dependence of the system on the heat sink
- ◆ No thermal collapse in parallel devices

**Application**

- ◆ Switching mode power supply, AC/DC converter
- ◆ Power factor correction
- ◆ Motor drive
- ◆ PV inverter and wind turbine



**Absolute Maximum Rating (Ta=25°C, unless otherwise specified)**

Parameter	Symbol	Test conditions	Value	Unit
Peak repetitive reverse voltage	$V_{RRM}$		1200	V
Working Peak Reverse voltage	$V_{RWM}$		1200	V
DC Blocking Voltage	$V_{DC}$		1200	V
Average rectified output current	$I_{F(AV)}$	$T_C = 25^\circ C$	33	A
		$T_C = 125^\circ C$	16	
		$T_C = 150^\circ C$	10	
Forward repetitive peak current	$I_{FRM}$	$T_C = 25^\circ C, t_p = 10ms, \text{Half Sine Wave}$	44	A
		$T_C = 110^\circ C, t_p = 10ms, \text{Half Sine Wave}$	26	
Forward surge current	$I_{FSM}$	$T_C = 25^\circ C, t_p = 10ms, \text{Half Sine Wave}$	113	A
		$T_C = 110^\circ C, t_p = 10ms, \text{Half Sine Wave}$	110	
Power dissipation	$P_{tot}$	$T_C = 25^\circ C$	48	W
Junction temperature	$T_j$		-55 ~ +175	°C
Storage temperature	$T_{stg}$		-55 ~ +175	°C
Mounting Torque		M3 Screw	1	Nm
		6-32 Screw	8.8	lbf-in

Thermal characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance - Junction to Case	$R_{\theta JC}$	0.9	$^{\circ}\text{C}/\text{W}$

Electrical Characteristics ( $T_a=25^{\circ}\text{C}$  unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Forward voltage	$V_F$	$I_F = 10\text{ A}, T_j=25^{\circ}\text{C}$ $I_F = 10\text{ A}, T_j=175^{\circ}\text{C}$		1.5 2.0	1.8 3.0	V
Reverse current	$I_R$	$V_R = 1200\text{V}, T_j=25^{\circ}\text{C}$ $V_R = 1200\text{V}, T_j=175^{\circ}\text{C}$		35 65	200 4000	$\mu\text{A}$
Total capacitive charge	$Q_C$	$V_R = 800\text{V}, I_F = 10\text{A}$ $di/dt=200\text{A}/\mu\text{s}, T_j=25^{\circ}\text{C}$		56		nC
Total capacitance	C	$V_R = 0\text{V}, T_j=25^{\circ}\text{C}, f=1\text{MHz}$ $V_R = 400\text{V}, T_j=25^{\circ}\text{C}, f=1\text{MHz}$ $V_R = 800\text{V}, T_j=25^{\circ}\text{C}, f=1\text{MHz}$		777 51 44		pF
Capacitance stored energy	$E_C$	$V_R = 800\text{V}$		17		$\mu\text{J}$

Typical Characteristics




Figure 1. Forward Characteristics




Figure 2. Reverse Characteristics




Figure 3 Current Derating




Figure 4 Power Derating




Figure 5. Capacitance vs reverse voltage





Figure 6. Total Capacitance charge vs reverse voltage

**Marking Diagram**



**Ordering information**

Model name	Package	Unit Weight	Base Quantity	Packing Quantity
YFWD310120AC	TO-220AC	0.067oz(1.9g)	50pcs/tube	1000PCS/Box 5000PCS/Carton

**Package Dimensions**

**TO-220AC**

Symbol	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	10.15	10.35	0.400	0.407
B	2.65	2.95	0.104	0.116
C	3.70	3.90	0.146	0.154
D	28.5	29.5	1.12	1.16
E	1.3	1.45	0.051	0.057
F	0.8	1.1	0.031	0.043
G	2.9	3.3	0.114	0.130
H	15.0	16.0	0.591	0.630
I	0.38	0.42	0.015	0.017
J	4.45	4.55	0.175	0.179
K	1.25	1.35	0.049	0.053
L	6.35	6.55	0.250	0.258
M	Typ5.08		Typ0.2	
N	Typ2.54		Typ0.1	
O	0.76	0.84	0.030	0.033
P	3.1	3.3	0.122	0.130

## Disclaimer

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.