

**HIGH CURRENT GLASS PASSIVATED SINGLE_PHASE
BRIDGE RECTIFIR**

Voltage - 1600V


Forward Current - 35 A

FEATURES

- ♦The plastic package has Underwriters Laboratory flammability recognition 94V-0
- ♦Integrally molded heatsink provide very low thermal resistance for maximum heat dissipation
- ♦Universal 3_way terminals; snap_on, wire wrap_around, or P.C. Board mounting
- ♦Surge overload ratings to 400 Amperes
- ♦Glass passivated chip junctions
- ♦High temperature soldering guaranteed: 260°C/10 seconds at 5lbs., (2.3kg)tension

MECHANICAL DATA

- ♦Case:BR
- ♦Terminals: Solderable per MIL-STD-202, Method208
- ♦Weight: 19.3 grams



Absolute MAX rating

Parameter	Symbols	BR3516	Units
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	1600	V
Maximum RMS voltage	V_{RMS}	1120	V
Maximum DC Blocking Voltage	V_{DC}	1600	V
Average rectified forward current,50Hz Sine wave resistance load $T_c=85^{\circ}\text{C}$	I_o	35	A
Peak Surge forward Current Non-repetitive 50Hz 10ms Sine wave $T_j=25^{\circ}\text{C}$	I_{FSM}	450	A
Dielectric strength,Terminals to case AC 1 minute	V_{dia}	2	kv
Forward Voltage $I_F=17.5\text{A}$	V_F	1.05	V
Reverse current	I_R	10	μA
Thermal reslstance,Junction to Case	$R_{\theta JC}$	1.5	$^{\circ}\text{C/W}$
Storage Temperature	T_{stg}	-40 ~ 150	$^{\circ}\text{C}$
Openrating junction Temperature	T_j	150	$^{\circ}\text{C}$

Rating and Characteristic Curves

FIG. 1
TYPICAL FORWARD CURRENT
DERATING CURVE




FIG. 2
MAXIMUM NON-REPETITIVE FORWARD
SURGE CURRENT




FIG. 3
TYPICAL INSTANTANEOUS
FORWARD CHARACTERISTICS






FIG. 4
TYPICAL REVERSE CHARACTERISTICS



Marking Diagram



Ordering information

Package	Packing Description	Packing Quantity
BR	bulk	50PCS/Box 500PCS/Carton

Package Dimensions

BR

Dim.	Millimeter(mm)		Dimensions inInch	
	Min.	Max.	Min.	Max.
A	13.90	14.90	0.547	0.587
B	15.70	16.70	0.618	0.657
C	4.50	5.50	0.177	0.217
D	18.00	19.00	0.709	0.748
E	15.70	16.70	0.618	0.657
F	31.0	32.0	1.220	1.260
G	0.60	1.00	0.024	0.256
H	6.10	6.50	0.240	0.256
I	8.50	9.50	0.335	0.374
J	22.00	24.00	0.866	0.945

Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.