


NPN Transistors

Features

- For AF driver and output stages
- High collector current
- Low collector-emitter saturation voltage
- Complementary to BCP51,BCP52,BCP53



Absolute Maximum Rating (Ta=25℃)

Parameter	Symbol	BCP54	BCP55	BCP56	Unit
Collector - Base Voltage	V _{CB0}	45	60	100	V
Collector - Emitter Voltage	V _{CEO}	45	60	80	
Emitter - Base Voltage	V _{EB0}	5			
Collector Current - Continuous	I _C	1			A
Collector Power Dissipation	P _C	1.5			W
Thermal Resistance Junction to Ambient	R _{θJA}	83.3			°C/W
Junction Temperature	T _J	150			°C
Storage Temperature Range	T _{stg}	-65 to 150			









Electrical Characteristics (Ta=25℃)

Parameter		Symbol	Test Conditions	Min	Typ	Max	Unit
Collector- base breakdown voltage	BCP54	V _{CBO}	I _C = 100 μA, I _E = 0	45			V
	BCP55			60			
	BCP56			100			
Collector- emitter breakdown voltage	BCP54	V _{CEO}	I _C = 10 mA, I _B = 0	45			
	BCP55			60			
	BCP56			80			
Emitter - base breakdown voltage		V _{EBO}	I _E = 100 μA, I _C = 0	5			
Collector-base cut-off current	BCP54	I _{CBO}	V _{CB} = 45 V, I _E = 0			0.1	uA
	BCP55		V _{CB} = 60 V, I _E = 0				
	BCP56		V _{CB} = 100 V, I _E = 0				
Emitter cut-off current		I _{EBO}	V _{EB} = 5V, I _C =0			0.1	
Collector-emitter saturation voltage		V _{CE(sat)}	I _C =500 mA, I _B =50mA			0.5	V
Base - emitter saturation voltage		V _{BE(sat)}	I _C =500 mA, I _B =50mA			1.2	
Base-emitter voltage		V _{BE}	V _{CE} = 2V, I _C = 500mA			1	
DC current gain		h _{FE(1)}	V _{CE} = 2V, I _C = 5mA	25			
		h _{FE(2)}	V _{CE} = 2V, I _C = 150mA	63		250	
		h _{FE(3)}	V _{CE} = 2V, I _C = 500mA	25			
Transition frequency		f _T	V _{CE} = 10V, I _C = 50mA, f=100MHz	100			MHz

h_{FE} Classification

Rank	BCP54,BCP55,BCP56	BCP54-10,BCP55-10,BCP56-10	BCP54-16,BCP55-16,BCP56-16
Range	63-250	63-160	100-250
Marking	BCP54,BCP55,BCP56	BCP54 10,BCP55 10,BCP56 10	BCP54 16,BCP55 16,BCP56 16

Typical Characteristics



Ordering information


Package	Packing Description	Base Quantity	Packing Quantity
SOT-223	Tape/Reel, 7" reel	1000pcs/Reel	6000PCS/Box 30000PCS/Carton
	Tape/Reel, 13" reel	2500pcs/Reel	5000PCS/Box 30000PCS/Carton

Package Dimensions

SOT-223

Dlm	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	1.50	1.80	0.059	0.071
A1	0.00	0.10	0.000	0.004
A2	1.50	1.70	0.059	0.067
b	0.65	0.75	0.026	0.030
c	0.20	0.30	0.008	0.012
D	6.40	6.60	0.252	0.260
D1	2.90	3.10	0.114	0.122
E	3.30	3.70	0.130	0.146
E1	6.85	7.15	0.270	0.281
e	2.20	2.40	0.087	0.094
e1	4.40	4.80	0.173	0.189
L	1.65	1.85	0.065	0.073
L1	0.90	1.15	0.035	0.045

The recommended mounting pad size



Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.