

60A Glass Passivated Single-Phase Bridge Rectifier

Reverse Voltage - 800 to 1600 V


Forward Current - 60A

FEATURES

- ◆Glass passivated chip
- ◆Low reverse leakage current
- ◆High surge current capability
- ◆Case to Terminal Isolation Voltage 2500V

MECHANICAL DATA

- ◆Case: SGBJ
- ◆Marking/Polarity: Marked on Body
- ◆Weight: About 11.60grams



Maximum Ratings and Thermal Characteristics @ Ta = 25°C unless otherwise noted

Parameter	Symbols	SGBJ6008	SGBJ6010	SGBJ6012	SGBJ6014	SGBJ6016	Units
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	800	1000	1200	1400	1600	V
Maximum RMS voltage	V_{RMS}	900	1100	1300	1500	1700	V
Maximum DC Blocking Voltage	V_{DC}	800	1000	1200	1400	1600	V
Maximum average forward output rectified current $T_A=120^{\circ}C$	$I_{F(AV)}$	60					A
Forward Voltage Per Leg @ $I_F=30A$	V_F	1.1					V
Peak surge forward current, 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	600					A
Rating for fusing, $1ms < t < 8.3ms$, $T_j=25^{\circ}C$, Rating of per diode	I^2t	1494					A ² S
Rms isolation voltage from case to leads	V_{isol}	2500					V
Operating Junction and storage temperature range	T_j, T_{stg}	-55 ~ +150					°C
Maximum DC reverse current at rated DC blocking voltage per leg $T_A=25^{\circ}C$ $T_A=125^{\circ}C$	I_R	5 500					uA
Typical Junction Capacitance	C_J	160					pF
Maximum thermal resistance per leg	$R_{\theta JC}$	0.7					°C/W

Note:

(1) Junction to case with heatsink

(2) Recommended mounting position is to bolt down on heatsink with silicone thermal compound for maximum heat transfer with M3 screw .

Characteristics(Typical)

Fig 1-forwardCurrent derating Curve




Fig.2-Maximum Non-Repetitive Surge Currnet




Fig.3-Typical Reverse Characteristics






Fig.4-Typical Forwaed Characteristics



Marking Diagram



Ordering information

Package	Packing Description	Packing Quantity
SGBJ	bulk	200PCS/Box 2000PCS/Carton

Package Dimensions

SGBJ

Dim.	Millimeter(mm)		DimensionsinInch	
	Min.	Max.	Min.	Max.
A	34.50	35.50	1.36	1.40
B	24.50	25.50	0.96	1.00
C	2.90	3.50	0.11	0.14
D	16.60	17.60	0.65	0.69
E	3.70	4.30	0.15	0.17
F	2.20	2.80	0.09	0.11
G	2.00	2.60	0.08	0.10
H	0.90	1.10	0.04	0.04
I	7.20	7.80	0.28	0.31
J	4.30	4.90	0.17	0.19
K	3.40	4.00	0.13	0.16
L	0.20	0.80	0.01	0.03
M	13.80	14.40	0.54	0.57
N	2.50	2.90	0.10	0.11
O	0.55	0.75	0.02	0.03

Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.